

Product catalog

Semi-Trailer Expandable Commercial Venue

A mobile, foldable and rapidly deployable multifunctional commercial space. The expandable structure is carried by a semi-trailer and can be separated when required. This product is not offered for use in Europe or Canada.



53FT · 15 × 12 m

180 m²

English · mbfdspaces.com

01

Platforms and dimensions

The 15.7 m external-length platform has 13.5 m of internal usable length. The 53FT platform has 15 m of internal usable length. At 12 m expanded width, the 53FT configuration provides 180 m². At 10 m expanded width, the same internal length gives 150 m².

02

Transport width and destination

A configuration with approximately 2.55 m folded width generally expands to 10 m. Another referenced configuration folds to approximately 2.85 m and expands to 12 m. These dimensions do not by themselves establish road approval. Suitability requires destination-specific review; container-based alternatives are available for Europe and Canada.

03

Deployment and capacity

A referenced configuration takes approximately 25 minutes to open or close and is normally operated by one trained person. Initial commissioning guidance is recommended. A referenced event arrangement may accommodate approximately 200–280 people, depending on layout, exits and local requirements. The complete unit weighs approximately 31 tons, depending on equipment.

04

Hydraulic system and maintenance

The referenced industrial hydraulic system uses 6 main load-bearing hydraulic units and 20 auxiliary support units. The referenced oil is L-HM 32 anti-wear hydraulic oil. Replace it annually or after approximately 50–100 deployment cycles, whichever comes first, subject to the delivered manual.

05

Site and operating conditions

The site should be basically level and suitable for the supports and loads. Referenced values include wind resistance up to 90 km/h and approximately 30 tons of distributed floor load; confirm their applicability to the quoted configuration. Close and secure the structure in severe weather. Concentrated loads require separate review.

06

Power architecture

The approximately 10 kW onboard generator powers the hydraulic system, not hall appliances. A separate 45–50 kW silent diesel generator is a referenced off-grid option for hall power. Final sizing depends on electrical loads. Voltage, frequency and electrical configuration are agreed for the destination.

07

Standard configuration

The quoted scope may include the steel structure, hydraulic system, flooring, wall panels, glazing, electrical systems, basic lighting, air conditioning and surround sound. Confirm quantities and equipment in the signed quotation. Furniture is not included as standard.

08

Optional enhancements

Immersive projection and visual effects, LED displays, fire protection, an accessible lift and perimeter railing can be discussed. Furniture sourcing assistance is available on request. Final equipment and installation requirements depend on the project.

09

Commercial applications

Party halls, wedding venues, nightclubs, restaurants, exhibitions, pop-up shops, mobile churches, supermarkets and corporate events are possible applications. Cinema, fitness, broadcast, esports and emergency-support layouts are concepts requiring project-specific design, equipment and approvals.

10

Business planning

The venue is a reusable commercial asset that can move between locations and support different operating formats. Assess site costs, transport, staffing, maintenance, utilities and expected bookings when preparing a business plan. Revenue and return on investment are not guaranteed.

11

Price and production


The typical reference price range is USD 90,000–120,000 depending on configuration. Most units are made to order. Production timing and all inclusions are confirmed after dimensions, finishes and equipment are agreed.

12

Shipping, support and warranty

RoRo shipping is commonly used; breakbulk is an alternative. Confirm destination ports, inland transport and commissioning responsibilities. Support can include manuals, installation videos, remote assistance and agreed on-site support. Referenced warranty coverage is 3 years for main structural components and 1 year for electrical components, subject to the signed contract.

Gallery & films



[Read online ↗](#)

Global sales FAQ

1. What is the price?

The price depends on configuration. A typical reference range is USD 90,000–120,000. The final quotation depends on platform, dimensions, interior, equipment and destination requirements.

2. What is this product?

A mobile, foldable and rapidly deployable multifunctional commercial space. Depending on the selected platform, it uses a container-based structure or a semi-trailer platform with an expandable structure.

3. Is it a building or a vehicle?

Classification varies by local regulation. It may be treated as a mobile commercial space, modular or temporary structure, or—in relevant configurations—a semi-trailer RV. Local authorities determine the final classification.

4. What can it be used for?

Applications include party halls, nightclubs, bars, restaurants, wedding venues, exhibitions, pop-up stores, event centres, mobile churches, supermarkets and corporate event spaces.

Global sales FAQ

5. What sizes are available?

The documented 45FT container configuration has a deployed interior of 10.4 × 10.3 m. Referenced semi-trailer configurations include 15.7 m and 53 ft external lengths, with 13.5 m and 15 m internal lengths respectively. Customized designs may be evaluated.

6. What folded widths are available for semi-trailer systems?

A road-width-oriented configuration may fold to 2.55 m and expand to 10 m. Another referenced configuration folds to approximately 2.85 m and expands to 12 m. Selection depends on destination requirements.

7. Which configuration produces 180 m²?

The referenced 180 m² dimensional combination uses the 53-foot platform with 15 m internal length and 12 m deployed width.

8. What is the referenced total weight?

The complete semi-trailer unit is approximately 31 tons depending on configuration. The referenced 45FT container-based configuration has an approximate transport weight of 23,000 kg.

Global sales FAQ

9. How many people can it accommodate?

Capacity depends on layout, exits and local rules. A semi-trailer event layout may typically accommodate around 200–280 people. For the 45FT system, 13 round tables with 10 diners each is an example of approximately 130 dining guests—not a maximum occupancy statement.

10. How long does opening or closing take?

A referenced semi-trailer system normally takes approximately 25 minutes to open or close. Timing varies with configuration, site and operator experience.

11. How many people are needed for operation?

The referenced semi-trailer deployment system can normally be operated by one trained person. Site safety procedures may require additional personnel.

12. Is a professional technician required?

Technical guidance is recommended for initial installation and commissioning. After training, the customer can operate the system independently according to the manuals and safety procedures.

Global sales FAQ

13. What is the wind resistance?

A referenced deployed configuration is specified for wind speeds up to 90 km/h. This claim must be confirmed for the quoted configuration. In severe weather the structure should be closed and secured.

14. What are the ground requirements?

The site should be basically level and suitable for the loads and supports. A complex permanent foundation may not be required, but site conditions must be assessed for each project.

15. What is the floor load capacity?

A referenced interior floor structure is described as supporting approximately 30 tons of distributed load. The applicable load definition and configuration must be confirmed in project documentation.

16. What hydraulic system is used?

The semi-trailer platform uses an industrial hydraulic deployment system with 6 main load-bearing hydraulic units and 20 auxiliary support units in the referenced configuration.

Global sales FAQ

17. How often should hydraulic oil be replaced?

Normally once per year or after approximately 50–100 hydraulic deployment cycles, whichever comes first, subject to the maintenance manual and operating conditions.

18. What hydraulic oil is used?

The standard referenced oil is L-HM 32 anti-wear hydraulic oil. Suitability should be confirmed for local climate and the delivered system.

19. Does it include a built-in generator?

A generator of approximately 10 kW may be installed under the semi-trailer to power the hydraulic system. It is not intended to power appliances or electrical equipment inside the hall.

20. What if there is no grid power?

For remote sites, a 45–50 kW silent diesel generator may be used as a project reference for hall power. Final sizing depends on the complete electrical load.

Global sales FAQ

21. Can the electrical system be adapted by country?

Yes. Voltage, frequency and electrical standards can be configured according to the destination and quoted project requirements.

22. What is normally included?

A referenced standard configuration may include the main steel structure, hydraulic system, flooring, wall and window systems, electrical and basic lighting systems, air conditioning and surround sound. The signed quotation defines the actual scope.

23. What optional features are available?

Options may include immersive lighting and visual systems, LED displays, fire protection systems, an accessible lift platform and external perimeter railing.

24. Is furniture included?

Furniture is not included in the standard quotation. MBFD can assist with purchasing when requested.

Global sales FAQ

25. Can the semi-trailer and expandable structure be separated?

Yes. In the semi-trailer configuration, the expandable structure can be treated as cargo carried by the trailer and can be separated when required.

26. How is it transported?

RoRo shipping is commonly used for semi-trailer units. Breakbulk shipping may also be used for large equipment. The 45FT container-based configuration is non-stackable and requires an appropriate non-stacking transport plan.

27. Can it be shipped worldwide?

It can be shipped to most countries and regions. The final method depends on ports, inland transport conditions, product platform and project requirements.

28. Where is the semi-trailer version available?

It may be considered for selected markets including the United States, South America, Africa, the Middle East and Southeast Asia. It is not offered for use in Europe or Canada; container-based alternatives are available there.

Global sales FAQ

29. Do you provide installation and technical support?

Support can include installation videos, operation manuals, remote assistance and on-site support when required and agreed.

30. What is the production time?

Production time depends on final configuration, customization and order details. The schedule is confirmed when the order is placed. A referenced 45FT production period is approximately 90 days.

31. Is it available from stock?

Most units are manufactured to order according to customer configuration and project requirements.

32. Do you provide compliance support?

Yes. Relevant technical documents and certification support can be provided according to the project and destination. Local approval remains subject to local authorities.

Global sales FAQ

33. What is the warranty?

Referenced coverage is 3 years for main structural components and 1 year for electrical components, subject to the signed contract, exclusions and maintenance requirements.

34. Why choose an expandable commercial space?

It is a mobile and reusable commercial asset that can reduce deployment time, support flexible site selection and serve different commercial opportunities without functioning like a conventional permanent building.

Contact

Zhongfeng Huashu (Zhejiang) Intelligent Technology Co., Ltd.

WhatsApp / WeChat: +86 177 0524 0212

joe@mobifold.com

WhatsApp ↗

mbfdspaces.com

Buying guides

Read online ↗